



AUSTIN POWDER

A TRADITION OF SAFETY, STRENGTH AND SERVICE.

Eagle®

High-Density Cast Explosive for primer applications.

DESCRIPTION

Austin's Eagle family of cast boosters are high-density molecular explosives designed to produce high detonation pressures for optimum initiation of blasting agents. Eagles can accommodate detonators up to 4" (101.5mm) in length. The Eagle family of cast boosters are designed to be initiated by non-electric, electric and electronic detonators that are classified as a minimum of #8 strength (450mg or greater PETN) base charge. ***Eagle boosters are not designed for use with detonating cord.***

BENEFITS

- Eagle cast boosters detonate in excess of 24,000 ft. /sec (7,380 m/sec).
- Over 225 kb of detonation pressure ensures optimum steady state velocity for blasting agents.
- Excellent shelf life, highly resistant to water and oil.
- Fully enclosed detonator well with internal detonator locking device and through tunnel.
- High visibility, impact resistant "fluorescent orange" polypropylene that is resistant to -40F to +150F for standard Eagle boosters.
- High visibility, impact resistant "yellow" polypropylene that is resistant to -40F to +150F for Eagle E-Star Boosters (internal brass sleeve).



SAFETY

Eagle cast boosters are manufactured with molecular explosives consisting of PETN and TNT, both of which are sensitive to severe impact, heat or friction. As with all explosives, Eagle boosters must be transported, stored and handled with care. Avoid any impact with solid surfaces.

Eagle Cast Boosters

DIMENSIONS & TYPICAL USES

Eagle boosters are not designed for use with detonating cord

Product Name	Weight		Outside Diameter		Length		Units Per Case	Typical Uses
	[oz]	[g]	[in]	[mm]	[in]	[mm]	Units	
Eagle 225	8	225	1.7	43	4.8	123	64	Priming blasting agents in holes of 2 "diameter or larger.
Eagle 340	12	340	2.1	53	4.8	123	49	Priming blasting agents in holes of 2.5 "diameter or larger.
Eagle 450	16	450	2.3	58	4.8	123	36	Priming blasting agents in holes of 3.0" diameter or larger.
Eagle 900	32	900	3.1	78	4.8	123	18	Priming blasting agents in holes of 4" diameter or larger

Product Name	Weight		Outside Diameter		Length		Units Per Case	Typical Uses
	[oz]	[g]	[in]	[mm]	[in]	[mm]	Units	
Eagle E-Star 225	8	225	1.7	43	4.8	123	64	Priming blasting agents in holes of 2 "diameter or larger. <i>Electronic Detonator Only</i>
Eagle E-Star 340	12	340	2.1	53	4.8	123	49	Priming blasting agents in holes of 2.5 "diameter or larger. <i>Electronic Detonator Only</i>
Eagle E-Star 450	16	450	2.3	58	4.8	123	36	Priming blasting agents in holes of 3.0" diameter or larger. <i>Electronic Detonator Only</i>
Eagle E-Star 900	32	900	3.1	78	4.8	123	18	Priming blasting agents in holes of 4" diameter or larger. <i>Electronic Detonator Only</i>



For more information and service locations in your area, please contact Austin Powder Company's headquarters:

Austin Powder Company
25800 Science Park Drive
Cleveland, Ohio, USA 44122

Phone: 1-800-321-0752
Fax: 1-216-464-4418
Web: www.austinpowder.com

SHELF LIFE

Five years from date of manufacture under good storage

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

UN CLASSIFICATION

Shipping Name: Boosters
Class & Division: 1.1D
ID Number: UN 0042

DOT REFERENCE NUMBER

EX-1993030285

IN CASE OF EMERGENCY CALL

CHEMTREC 1-800-424-9300
Maritime 1-703-527-3887
International: dial access code:
+ 00-1-703-527-3887

Disclaimer of Warranties and Limitations of Liabilities

"Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages."