



Emulex[®] 900 Series

AUSTIN POWDER

A TRADITION OF SAFETY, STRENGTH AND SERVICE.

Detonator Sensitive Emulsion

DESCRIPTION

Emulex 900 series is a detonator sensitive emulsion explosive with putty like texture packaged in plastic film, tampable plastic film or rigid paper tube cartridges.

BENEFITS

- Excellent fragmentation when proper grade is matched to the rock conditions.
- >99% borehole coupling when loading cut or tamped cartridges.
- Excellent water resistance in all grades.
- Superior resistance to dynamic pre-compression.



PROPERTIES

Product	Density [g/cc]	RBS [‡]	Fume Class	Water Resistance	VOD	
					[ft/s]	[m/s]
Emulex 917	1.17	107	1	Excellent	17,000	5,577
Emulex 927	1.17	142	2	Excellent	16,500	5,413
Emulex 937	1.19	162	2	Excellent	15,500	5,085

[‡] Energy is calculated using TIGER, a thermo-dynamic computer code used by Austin Powder Company. Other computer codes may give different values. ANFO = 100 @ 0.82 g/cc.

PRIMING

Use a high strength detonator (Rock*Star[®], Shock*Star[®] or equivalent). If product temperature is below 0° F (-17° C), prime with a minimum of a Gold Nugget[™] (8 gm) cast booster. This product is not designed for use with any strength of detonating cord.

Emulex 900 Series

Cartridge Size		917	927	937	Cartridge Weight		Case Count 50 lb / 22.5 kg
[in]	[mm]				[lb]	[kg]	
1 x 12	25 x 300	V, PMP	V, PMP	---	0.38	0.17	132
1 ¼ x 12	32 x 300	V, PMP	V, PMP	---	0.67	0.30	75
1 ½ x 12	38 x 300	V, PMP	V, PMP	---	0.88	0.40	57
1 ¼ x 16	32 x 400	---	AT	---	0.89	0.40	56
1 ½ x 16	38 x 400	V, PMP	V, AT, PMP	---	1.28	0.58	39
1 ¾ x 16	44 x 400	V	V, AT	---	1.61	0.73	31
2 x 16	50 x 400	V	V, BN	V, BN	2.27	1.03	22
2 ¼ x 16	57 x 400	V	V, BN	V, BN	2.50	1.13	20
2 ½ x 16	63 x 400	V	V, BN	V, BN	3.33	1.51	15
2 ¾ x 16	69 x 400	V	V, BN	V, BN	3.85	1.75	13
3 x 16	75 x 400	V	V, BN	V, BN	4.55	2.06	11
3 ¼ x 16	82 x 400	V	V, BN	V, BN	5.00	2.27	10
3 ½ x 16	88 x 400	V	V, BN	V, BN	6.25	2.84	8

V = Plastic Film; PMP = Poly Mylar Poly Laminate Film (tampable); AT, BN = Rigid Paper Tube

--- Not Available

Note: All dimensions and weights are nominal.



For more information and service locations in your area, please contact:

Austin Powder Company

25800 Science Park Drive
Cleveland, Ohio, USA 44122

Phone: 1-800-321-0752

Fax: 1-216-464-4418

Web: www.austinpowder.com

Email: info@austinpowder.com

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

SHELF LIFE

One year from date of manufacture under good storage conditions.

UN CLASSIFICATION

Shipping Name: Explosive, Blasting, Type E

Class & Division: 1.1D

ID Number: UN0241

DOT REFERENCE NUMBER

EX-9305177

Disclaimer of Warranties and Limitations of Liabilities

"Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages."