


# A-140 F

Fluid Disabled Resistorized  
Instantaneous RDX Detonator

*Austin Powder Company*

## CONSTRUCTION FEATURES



A-140 F	
Shell Length	49 mm / 1.93 "
Base Charge	5 grains RDX (0.325 gram)
No-Fire Current ( approx.) (Based on a constant voltage for 1 minute)	0.2 amperes
All-Fire Current ( approx.)	0.8 amperes
Minimum Firing Current (approx.)	0.5 amperes
<b>Resistors in Series with Bridgewire</b>	<b>(2) 27 ohm</b>
Leg to Leg Resistance Plus 0.032 for each foot of duplex wire	51 to 60 ohm + 0.27/0.32 ohm
High Temperature Performance	1 hr. at 350°F
<b>Electrostatic Sensitivity Energy Value</b> (Double leg to shell capacitor discharge energy level)	<b>781 mJ</b>

- **Antistatic sleeve and spark gap protect against static electricity.**
- **Leg wires are high temperature Teflon insulated 22 gauge four feet long copper leg wires.**

**DO NOT REMOVE TAPE UNTIL IMMEDIATELY PRIOR TO USE !**

**P.I.B A-140F/0402**

**Disclaimer of Warranties and Limitation of Liability**

"Product described in this bulletin are sold by Austin Powder Company without warranties; express, implied, or by statutory or as to **MECHANABILITY**, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for damages or loss of anticipated profits, consequential damages or incidental damages."



**Austin Powder Company**

25800 Science Park Drive  
Cleveland, Ohio 44122 USA  
216-464-2400 or 800-321-0752  
Fax 216-464-4418