



Rock★Star® Detonators

AUSTIN POWDER

A TRADITION OF SAFETY, STRENGTH AND SERVICE.

Electric Millisecond and Long Period
Delay Detonators

DESCRIPTION

Rock★Star electric detonators are designed to provide the precise control necessary to produce accurate and consistent blasting results in a variety of blasting applications in the mining, quarrying and construction industries.

BENEFITS

- 900 mg RDX and/or PETN base charge far exceeds the standard #8 strength detonator.
- Industries strongest aluminum shell reduces the possibility of water hammer effect.
- HDPE insulation for added protection from extraneous currents.
- Wide selection of delay intervals provide greater flexibility in blast design.



Electrical Data	
No Fire Current	0.25 amps
All Fire Current	1.00 amps
Series Ignition Current	1.50 amps
No Fire Impulse	2.5 mJ/ohms
All Fire Impulse	5.5 mJ/ohms
Electrostatic Sensitivity	
Double Wire to Shell	10 kV/300 pF/15 mJ
Pin to Pin	10 kV/300 pF/15 mJ

Properties & Packaging

Rock★Star MS Delay Sequence													
Delay #	0	1	2	3	4	5	6	7	8	9	10	11	12
MS Time	0	25	50	75	100	125	150	175	200	225	250	275	300
Delay #	13	14	15	16	17	18	19	20	22	24	26	28	30
MS Time	325	350	375	400	425	450	475	500	600	700	800	900	1000

Length	[ft]	16	20	24	30	40	60	80
	[m]	4.9	6.1	7.3	9.1	12.2	18.3	24.4
Total Resistance [Ω]*		1.6	1.78	1.9	1.65	1.85	2.25	2.7

* Includes fusehead resistance of 0.9 +/- 0.1 Ω.

Rock★Star Detonators

Rock★Star LP Delay Sequence *														
Delay #	0	1	2	3	4	5	6	7	8	9	10	11	12	13
MS Time	0	50	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500

* Available in 20' length only

Rock★Star MS and LP Packaging						
Length		Case Weight		Case Count	NEQ per Case [gr]	Wire Configuration
[ft]	[m]	[lb]	[kg]			
16	4.9	6.1	2.8	40	40	Short Fold
20	6.1	6.6	3.0	40	40	Short Fold
24	7.3	5.5	2.5	40	40	Short Fold
30	9.1	6.6	3.0	15	15	Long Fold
40	12.2	6.6	3.0	15	15	Long Fold
60	18.3	6.6	3.0	10	10	Long Fold
80	24.4	7.7	3.5	10	10	Long Fold

* All Rock★Star 24' (7.3 m) and less, have 22 AWG (0.6 mm) copper wire.

** All Rock★Star 30' (9.1 m) and more, have 20 AWG (0.8 mm) copper wire.

Case Dimension: 11 1/4" x 7 5/8" x 5"
286mm x 194mm x 127mm

Rock★Star MS and LP Recommended Firing Current				
Circuit Type	Single Detonator	Single Series	Parallel Series	Parallel
DC [Amps]	0.5	1.5	1.5	1.0–10.0/Detonator
AC [Amps]	0.5	2.0	2.0	1.0–10.0/Detonator



For more information and service locations in your area, please contact Austin Powder Company's headquarters:

Austin Powder Company
25800 Science Park Drive
Cleveland, Ohio, USA 44122

Phone: 1-800-321-0752
Fax: 1-216-464-4418
Web: www.austinpowder.com
Email: info@austinpowder.com

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

SHELF LIFE

For optimum accuracy, use within five years from date of manufacture under good storage conditions.

UN CLASSIFICATION

Shipping Name: Detonators, Electric
Class & Division: 1.4B
ID Number: UN 0255

DOT REFERENCE NUMBER

EX-2014020188

Disclaimer of Warranties and Limitations of Liabilities

"Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages."