



AUSTIN POWDER

A TRADITION OF SAFETY, STRENGTH AND SERVICE.

Shock★Star® MS Detonators

Non-Electric, Millisecond Delay Detonators

DESCRIPTION

Shock★Star MS Series In-Hole Delays are available in a sequence of 31 whole number periods from instantaneous (0 ms) to 1000 ms. They are designed to be used as down-hole detonators for the initiation of cast boosters, high explosives or pneumatically loaded ANFO. In-Hole Delays come equipped with a T-Connector for compatibility with detonating cord initiation or can be initiated by an electric or non-electric detonator or approved shock tube starter device.

BENEFITS

- 900 mg base charge of PETN to ensure strong initiation energy under even the most extreme conditions.
- Delay composition encased in a zinc jacket to prevent performance loss due to transient pressure from nearby detonating holes.
- Equipped with a tear-proof delay tag that lists DSC, delay time, delay period and length of the detonator.
- Manufactured with bright yellow shock tubing for high visibility.



Shock★Star MS Detonators

LENGTH, DELAY & PACKAGING

IN-HOLE MS DETONATORS				
Length		Coil Style	Quantity	NEQ Grams
(ft)	(m)			
12	3.7	Fast 8	70	70
16	4.9	Fast 8	70	70
20	6.1	Fast 8	60	60
30	9.2	Fast 8	60	60
40	12.2	Fast 8	50	50
50	15.3	Fast 8	40	40
60	18.3	Fast 8	40	40
80	24.4	Fast 8X	30	30
100	30.5	Fast 8X	20	20
120	36.6	Fast 8X	20	20
130	39.7	Spool	10	10
150	45.8	Spool	10	10
160	48.8	Spool	10	10
180	54.9	Spool	10	10
200	61.0	Spool	10	10

Available Periods – MS Delays						
Period#	0	1	2	3	4	5
Delay (ms)	0	25	50	75	100	125
Period#	6	7	8	9	10	11
Delay (ms)	150	175	200	225	250	275
Period#	12	13	14	15	16	17
Delay (ms)	300	325	350	375	400	425
Period#	18	19	20	22	24	26
Delay (ms)	450	475	500	600	700	800
Period#	28	30				
Delay (ms)	900	1000				



For more information and service locations in your area, please contact Austin Powder Company's headquarters:

Austin Powder Company
25800 Science Park Drive
Cleveland, Ohio, USA 44122

Phone: 1-800-321-0752
Fax: 1-216-464-4418
Web: www.austinpowder.com
Email: info@austinpowder.com

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

SHELF LIFE

For optimum accuracy, use within three years from date of manufacture under good storage conditions.

UN CLASSIFICATION

Shipping Name: Detonator Assemblies, Non-Electric
Class & Division: 1.1B, 1.4B (depending on case count)
ID Number: UN 0361

DOT REFERENCE NUMBER

EX-2012070727
EX-2012081113

All Shock★Star non-electric detonators are manufactured by Austin Star Detonator Co., Brownsville, TX.

Disclaimer of Warranties and Limitations of Liabilities

"Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages."