



Seisprime™

High-Density Molecular Explosive

AUSTIN POWDER

A TRADITION OF SAFETY, STRENGTH AND SERVICE.

DESCRIPTION

Seisprime is formulated of a composite of high density, high velocity molecular explosives. Seisprime is engineered to produce over 240 kilo bars of detonation pressure. The rigid threaded plastic Seisprime cartridge is designed to accept an anchor point or top anchor, and is provided with two detonator wells. Seisprime has the longest “sleep time” of any commercial seismic explosive. The formulation suits the requirements of mini-hole, as well as deep hole seismic exploration. Use a high-strength Seismic detonator of 720mg PETN or greater for reliable initiation.

BENEFITS

- 24,500 fps detonation velocity produces excellent seismic pulse images.
- Formulated to achieve a higher detonation temperature and lower post detonation gas production than standard seismic Pentolite, Dynamites or Emulsions.
- Does not contain nitroglycerine or perchlorates.
- Full function reliability in all typical geophysical hole depths/water conditions.



Velocity of Detonation (mps / fps)	Detonation Pressure* (kilo bars)	Total Gas Generation* (liters / kg)	Energy* (MJ/kg)	Density (grams/cc)	Water Resistance
7,538 / 24,500	240	619	6.33	1.73	Excellent

*Detonation pressure, total gas generation and energy values are calculated using Tiger™, a well established thermodynamic computer code. Other computer codes may give different values.

Seisprime

PACKAGING

Product (kg / lbs.)	Cartridge Size** (mm / in.)	Quantity per case	Case Weigh (kg / lbs.)	Case Size (cm / inches)
Seisprime (0.5 / 1.1)	57 / 2 ¼	40	21.5 / 47.4 lb	32.4 x 44.4 x 29.8 12 ¾ x 17 ½ x 11 ¾
Seisprime (1.0 / 2.2)	57 / 2 ¼	20	21.5 / 47.4 lb	32.4 x 44.4 x 29.8 12 ¾ x 17 ½ x 11 ¾
Seisprime (2.0 / 4.4)	57 / 2 ¼	10	21.5 / 47.4 lb	33 x 78.1 x 11.7 13 x 30 ¾ x 4 ⅝
Seisprime (2.5 / 5.5)	57 / 2 ¼	10	25.9 / 57.0 lb	33 x 78.1 x 11.7 13 x 30 ¾ x 4 ⅝

*Available in other sizes upon request.



For more information and service locations in your area, please contact Austin Powder Company's headquarters:

Austin Powder Company
25800 Science Park Drive
Cleveland, Ohio, USA 44122

Phone: 1-800-321-0752
Fax: 1-216-464-4418
Web: www.austinpowder.com
Email: info@austinpowder.com

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

SHELF LIFE

Indefinite from date of manufacture under good storage conditions.

UN CLASSIFICATION

Shipping Name: Boosters
Class & Division: 1.1D
ID Number: UN 0042

DOT REFERENCE NUMBER

EX-1993030285

Disclaimer of Warranties and Limitations of Liabilities

"Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages."