

Static★Star™

PRODUCT INFORMATION BROCHURE

The Static★Star detonator is specifically designed for the harsh conditions encountered in a modern 3-D seismic survey. The two part pressed fit sealing plug, combined with a newly designed adhesion compound, ensures protection from the environment of salt and brackish waters for extended periods of time. With the largest base charge in the industry, Static★Star electric detonators will initiate all detonator sensitive seismic explosives.



ADVANTAGES

- 900 mg PETN base charge far exceeds the standard #8 strength detonator.
- Designed for extended sleep time in salt / brackish water use.
- Consistent break time when firing with 3-10 amperes DC current.
- No fire current of 0.45 amperes for extra protection from electrostatic discharge.
- Two part sealing plug for protection from water.
- Resistant to temperature extremes from -40°F / -40°C to 150°F / 66°C.
- # 20 AWG, high abrasion resistant, Yellow HDPE insulated wire.
- Protected primary explosive charge.

STANDARD TECHNICAL DESCRIPTION

Electric seismic detonator for the geophysical industry



AUSTIN POWDER

Austin Powder Company, 25800 Science Park Drive

Phone: 1-800-321-0752 | Fax: 1-216-464-4418 | Email: info@austinpowder.com | www.austinpowder.com



Static★Star

PROPERTIES and STANDARD PACKAGING DETAILS

Length		Ohms Resistance (Ω)	Case Count	Case Weight		NEQ per Case (gr)	Wire Configuration
Ft	Mt			Lbs	Kg		
12	3.7	0.84	20	5.3	2.4	20	Figure 8
24	7.3	1.08	20	5.7	2.6	20	Figure 8
35	10.7	1.31	15	5.7	2.6	15	Figure 8
45	13.7	1.50	10	4.5	2.1	10	Figure 8
55	16.8	1.72	10	5.4	2.5	10	Figure 8
65	19.8	1.92	10	6.3	2.9	10	Figure 8
85	25.9	2.33	10	8.8	4.0	10	Spooled
100	30.5	2.64	10	10.2	4.6	10	Spooled
120	36.6	3.05	10	11.6	5.2	10	Spooled
140	42.7	3.46	3	5.1	11.2	3	Spooled
160	48.8	3.87	3	5.7	12.6	3	Spooled
200	61.0	4.69	3	6.8	14.9	3	Spooled

*Other lengths available upon request

Electrical Data*	
No Fire Current	0.45 amps
All Fire Current	1.50 amps
Series Ignition Current	6.00 amps
No Fire Impulse	8 mJ/ohms
All Fire Impulse	16 mJ/ohms
Electrostatic Sensitivity	
Double Wire to Shell	20 kV/500 pF/100 mJ
Pin to Pin	10kV/500 pF/25mJ

* Meets or exceeds the IAGC and CAGC Recommended Product Testing Methods and Specifications for Conventional Bridge-wire type Electric Seismic Detonators for Use in Seismic Operations

STORAGE

Store in accordance with all applicable local, state, provincial and federal laws.

Case Dimension:	11 1/4" x 7 5/8" x 5"
	286mmx x194mm x 127mm

SHELF LIFE

For optimum accuracy, use within five years from date of manufacture under good storage conditions.

TRANSPORTATION DATA

UN CLASSIFICATION

Shipping Name: Detonators, Electric

Class & Division: 1.4B

ID Number: UN 0255

US DOT REFERENCE NUMBER

EX-2014020188

Disclaimer of Warranties and Limitations of Liabilities: Products described in this bulletin are sold by Austin Powder Company without warranty; express, implied or statutory or as to MERCHANTABILITY, except as expressly stated in Austin Powder's straight bill of lading. Under no circumstances shall seller be liable for loss of anticipated profits, consequential damages or incidental damages.

© 2020 Austin Powder Company. All rights reserved.

For more information and service locations in your area, please contact Austin Powder Company's headquarters:



AUSTIN POWDER

Austin Powder Company, 25800 Science Park Drive

Phone: 1-800-321-0752 | Fax: 1-216-464-4418 | Email: info@austinpowder.com | www.austinpowder.com



2/22/06 | 01/31/2020